


MINIATURE PC BOARD TYPE POWER RELAY

JS RELAYS



mm inch

FEATURES

- **Miniature size with universal terminal footprint**
- **High contact capacity: 10 A**
- **TV-5 type available (Standard type)**
1 Form A type → TV-5
1 Form C type → TV-5 (N.O. side only)
- **VDE, TÜV also approved**
- **Sealed construction for automatic cleaning (Standard type)**
- **Class B and F coil insulation type also available.**
- **EN60335-1 GWT compliant (Tested by VDE) type available**
- **Surge voltage 6 kV type also available**

About Cd-free contacts

We have introduced Cadmium free type products to reduce Environmental Hazardous Substances. (The suffix "F" should be added to the part number)
Please replace parts containing Cadmium with Cadmium-free products and evaluate them with your actual application before use because the life of a relay depends on the contact material and load.

RoHS Directive compatibility information
<http://www.nais-e.com/>

SPECIFICATIONS

Contact

| Types | | Standard type | Long endurance type |
|---|--|--|---|
| Arrangement | | 1 Form A, 1 Form C | 1 Form A |
| Initial contact resistance, max. (By voltage drop 6 V DC 1 A) | | 100 mΩ | |
| Contact material | | AgSnO ₂ type | |
| Rating (resistive load) | Nominal switching capacity | 10 A 250 V AC 10 A 125 V AC 6 A 277 V AC | 10 A 250 V AC 10 A 125 V AC 10 A 277 V AC |
| | Max. switching power | 2,500 VA | |
| | Max. switching voltage | 250 V AC, 100 V DC | |
| | Max. switching current | 10 A (AC), 5 A (DC) | |
| Min. switching capacity ^{#1} | | 100 mA, 5 V DC | |
| Expected life (min. ope.) | Mechanical (at 180 cpm) | 10 ⁷ | |
| | Electrical at 10 A 125 V AC, 6 A 277 V AC resistive (standard) 10 A 277 V AC resistive (High power) | 1×10 ⁵ | 2×10 ⁵ |
| | 10 A 250 V AC resistive (Standard: at 20 cpm) (High power: at 20 cpm, 105°C 221°F)** | 5 × 10 ⁴ (No contact only) | 1.2 × 10 ⁵ |

** Holding voltage should be 60% V of nominal voltage

Coil

| | |
|-------------------------|--------|
| Nominal operating power | 360 mW |
|-------------------------|--------|

^{#1} This value can change due to the switching frequency, environmental conditions, and desired reliability level, therefore it is recommended to check this with the actual load.

Remarks

*1 Detection current: 10mA

*2 Excluding contact bounce time

Characteristics

| Max. operating speed | | 20 cpm | |
|--|---------------------------|--|------------------------------------|
| Types | | Standard type | Long endurance type |
| Initial insulation resistance | | Min. 100 MΩ (at 500 V DC) | |
| Initial breakdown voltage*1 | Between open contacts | 750 Vrms for 1 min. | |
| | Between contacts and coil | 1,500 Vrms for 1 min. | |
| Operate time*2 (at nominal voltage) | | Max. 10 ms | |
| Release time (without diode)*2 (at nominal voltage) | | Max. 10 ms | |
| Temperature rise (at nominal voltage) | | Max. 35°C, resistive, nominal voltage applied to coil. Contact carrying current: 10A, at 70°C 158°F | |
| Shock resistance | Functional*3 | 98 m/s ² {10 G} | |
| | Destructive*4 | 980 m/s ² {100 G} | |
| Vibration resistance | Functional*5 | 10 to 55 Hz at double amplitude of 1.6 mm | |
| | Destructive | 10 to 55 Hz at double amplitude of 2 mm | |
| Conditions for operation, transport and storage*6 (Not freezing and condensing at low temperature) | Ambient temp.*7 | -40°C to +85°C -40°F to +185°F | -40°C to +105°C -40°F to +221°F |
| | Humidity | 5 to 85% R.H. | |
| Unit weight | | Approx. 12 g .423 oz | |

*3 Half-wave pulse of sine wave: 11ms; detection time: 10μs

*4 Half-wave pulse of sine wave: 6ms

*5 Detection time: 10μs

*6 Refer to 6. Conditions for operation, transport and storage mentioned in AMBIENT ENVIRONMENT

*7 When using relays in a high ambient temperature, consider the pick-up voltage rise due to the high temperature (a rise of approx. 0.4% V for each 1°C 33.8°F with 20°C 68°F as a reference) and use a coil impressed voltage that is within the maximum allowable voltage range.

TYPICAL APPLICATIONS

1. Home appliances
Air conditioner, heater, etc.
2. Automotive
Power-window, car antenna, door-lock, etc.
3. Office machines
PPC, facsimile, etc.
4. Vending machines

ORDERING INFORMATION

Ex. JS 1a F - B - 12V - F -

| Contact arrangement | Protective construction | Coil insulation class | Coil voltage (DC) | Contact material | Flame resistance and tracking resistance | Surge voltage |
|--|--|---|---------------------------|----------------------------|--|---------------|
| 1: 1 Form C (Standard) 1a: 1 Form A (Standard) 1aP: 1 Form A (Long endurance type) | Nil: Sealed type F: Flux-resistant type | Nil: Class E insulation B: Class B insulation F: Class F insulation | 5, 6, 9, 12, 18, 24, 48 V | F: AgSnO ₂ type | Nil: — T: EN60335-1 (Conform) | 6K: 6kV type |

Standard: UL/CSA, VDE, TÜV (Standard type)
UL/CSA, VDE (Long endurance type and EN60335-1 GWT compliant type)
UL/CSA (Surge voltage 6kV type)

- Notes: 1. Standard packing: Carton: 100 pcs. Case: 500 pcs.
2. When ordering TV rated (TV-5) types, please consult us.
3. Contact arrangement 1aP type is Flux-resistant type only (Class B insulation only).
4. Please inquire about the previous products (Cadmium containing parts).



COIL DATA

| Part No. | | | | | Nominal voltage, V DC | Pick-up voltage, V DC (max.) (at 20°C 68°F) | Drop-out voltage, V DC (min.) (at 20°C 68°F) | Coil resistance, Ω (±10%) (at 20°C 68°F) | Nominal operating current, mA (±10%) (at 20°C 68°F) | Nominal operating power, mW (at 20°C 68°F) | Max. allowable voltage (at 85°C 185°F) |
|---------------|-----------|---------------------|------------|---------------------|-----------------------|---|--|--|---|--|--|
| Standard type | | Long endurance type | | | | | | | | | |
| Sealed type | | Flux-resistant type | | Flux-resistant type | | | | | | | |
| 1 Form A | 1 Form C | 1 Form A | 1 Form C | 1 Form A | | | | | | | |
| JS1a-5V-F | JS1-5V-F | JS1aF-5V-F | JS1F-5V-F | JS1aPF-B-5V-F | 5 | 3.5 | 0.5 | 69.4 | 72 | 360 | 130%V of nominal voltage |
| JS1a-6V-F | JS1-6V-F | JS1aF-6V-F | JS1F-6V-F | JS1aPF-B-6V-F | 6 | 4.2 | 0.6 | 100 | 60 | | |
| JS1a-9V-F | JS1-9V-F | JS1aF-9V-F | JS1F-9V-F | JS1aPF-B-9V-F | 9 | 6.3 | 0.9 | 225 | 40 | | |
| JS1a-12V-F | JS1-12V-F | JS1aF-12V-F | JS1F-12V-F | JS1aPF-B-12V-F | 12 | 8.4 | 1.2 | 400 | 30 | | |
| JS1a-18V-F | JS1-18V-F | JS1aF-18V-F | JS1F-18V-F | JS1aPF-B-18V-F | 18 | 12.6 | 1.8 | 900 | 20 | | |
| JS1a-24V-F | JS1-24V-F | JS1aF-24V-F | JS1F-24V-F | JS1aPF-B-24V-F | 24 | 16.8 | 2.4 | 1,600 | 15 | | |
| JS1a-48V-F | JS1-48V-F | JS1aF-48V-F | JS1F-48V-F | JS1aPF-B-48V-F | 48 | 33.6 | 4.8 | 6,400 | 7.5 | | |

- Notes) 1. Class B and F coil insulation types available.
Ex) JS1aF-B-12V-F
JS1aF-F-12V-F
2. EN60335-1 GWT compliant types available. When ordering, please add suffix "T".
Ex) JS1aF-B-12V-F-T
3. Surge voltage 6kV types available. When ordering, please add suffix "6K" (except for Long endurance type and EN60335-1 GWT compliant type).
Ex) JS1aF-B-12V-F-6K



DIMENSIONS

mm inch





Note: Terminal No. 4 is only for Standard 1 Form C type
General tolerance: ±0.3 ±0.12

Schematic (Bottom view)




PC board pattern (Bottom view)




Tolerance: ±0.1 ±0.004

REFERENCE DATA


1. Maximum value for switching capacity




2. Operate/release time
Sample: 25 pcs., JS1-12V-F




3. Life curve
Ambient temperature: Room temperature




4-(1). Coil temperature rise
Sample: 5 pcs., JS1a-24V-F
Measured portion: Inside the coil
Contact current: 5 A



4-(2). Coil temperature rise
Sample: 5 pcs., JS1a-24V-F
Measured portion: Inside the coil
Contact current: 10 A



5. Ambient temperature characteristics
Sample: 6 pcs., JS1-12V-F



For Cautions for Use, see Relay Technical Information