


**PIN ASSIGNMENT**

**CN1**

No.	SYMBOL	No.	SYMBOL
1	FGND	11	D <sub>a</sub>
2	GND	12	D <sub>i</sub>
3	V <sub>cc</sub>	13	D <sub>i</sub>
4	V <sub>ee</sub>	14	D <sub>i</sub>
5	WR	15	D <sub>i</sub>
6	R <sub>DD</sub>	16	D <sub>s</sub>
7	CE	17	D <sub>s</sub>
8	C/D	18	D <sub>r</sub>
9	NC	19	FS
10	RESET	20	RV

**CN2**

No.	SYMBOL
1	V <sub>cc</sub>
2	NC
3	NC
4	NC
5	V <sub>ee</sub>



MEASURE	TOLERANCE			UNIT	DATE
	A	B	C		
L16	±0.1	±0.3	±1	MM	JAN. 9 '96
L6-L63	±0.2	±0.5	±1.5	MM	
63-L6290	±0.3	±0.8	±2	MM	
250-D6500	±0.5	±1.2	±3	MM	
SCRD	±0.8	±2	±4	MM	
ANGLE	±1°	±5°	±10°		

THROW	DATE	DATE	DATE
APPROVED	JAN. 9 '96		
CHECKED			
DRAWN			
K. NAKAMAI			

97.1.23  
 47114724

OPTREX CORPORATION  
 DIMENSIONAL OUTLINE  
 DMF-50773 CFL SERIES  
 UE-36773